

PARTIAL STORAGE HEATER



Advantages:

- **Easy Installation**
- **Safe, clean and easy to operate**
- **Slimline Radiators are 70 mm deep**
- **No maintenance required**
- **100% efficient**
- **No boiler, plumbing or pipe work required**

Type TT-KS S

- Manual, radio frequency or digitally integrated thermostat
- Fully controllable by either manual or digitally controlled thermostats with „open window function, adaptive start function and more...)
- Radiators come fully assembled with appropriate plugs and 1.5m of cable
- All radiators are powder coated in a white high quality enameled finish
- Supplied with wall fixing brackets
- Castors, feet stands or radiator supports can be ordered as optional extras

Using mobile:

This product is only suitable for well-insulated rooms or for occasional use.



Our „Standard“
Height: 63 cm
Depth: 7 cm



Standard control



Type	Power [Watt]	Dimensions [cm]	Protection class
TT-KS 500 S DSM RF X4	500	38 x 63 x 7	IP 20 IP 24
TT-KS 1000 S DSM RF X4	1000	68 x 63 x 7	IP 20 IP 24
TT-KS 1200 S Plus RF X4	1200	68 x 63 x 7	IP 20 IP 24
TT-KS 1500 S DSM RF X4	1500	98 x 63 x 7	IP 20 IP 24
TT-KS 1800 S DSM RF X4	1800	98 x 63 x 7	IP 20 IP 24
TT-KS 2000 S DSM RF X4	2000	128 x 63 x 7	IP 20 IP 24
TT-KS 2400 S DSM RF X4	2400	128 x 63 x 7	IP 20 IP 24
TT-KS 2800 S DSM RF X4	2800	158 x 63 x 7	IP 20 IP 24
s= Standard DSM = „DSM“-Thermostat RF = RF Receiver X4 = protection class IP 24			

- elegant finish safe, clean and easy to serve
- Fully controllable by either manual or digitally controlled (DSM) thermostats
- Just 70 mm deep
- No maintenance required
- 100% efficient
- Supplied with wall fixing brackets
- Castors, feet stands or radiator support ports can be ordered as optional extras
- Radiators come fully assembled with appropriate plugs and 1.5m of cable

With receiver RF



With „DSM“ - 24/7 digital programmable electronic thermostat, open window function, internet adjustable etc..



TECHNOTHERM a brand of Lucht LHZ GmbH & Co. KG
Reinhard-Schmidt-Str. 1 | 09217 Burgstädt
Telefon: +49 (0) 3724 66869 0
Telefax: +49 (0) 3724 66869 20
info@technotherm.de | www.technotherm.de

Subject to errors and technical amendments. Dimensions without guarantee! Edition 04/18